



TECHNICAL DATA SHEET

Order reference	DT025
Article number	813784

Date	6-21-06	Replaces	3-16-06	No. Pages	1
-------------	---------	-----------------	---------	------------------	---

Product Description:

Style	Drum Top Cover
Item Size (each)	56 cm diameter
Color	White
Composition	100% Polypropylene
Structure	A nonwoven mat of randomly oriented Micro-fibers [2-10 micron diameters]
Technology	Meltblown, 3-ply
Absorbency	Hydrophobic + Oleophilic
Bonding	Ultrasonic "Oil Drop Dimple" staggered pattern + Mechanical entanglement

Intended Application	Drum Top Cover of Low -Lint Chemical Resistant Sorbent for Oil, and Solvent Base Liquids
-----------------------------	--

Absorbency Capacity	26 l per bale (saturated; medium viscosity-12.5x)
----------------------------	---

Packaging Description:

Package configuration	Case	Pkg. Weight	2.6 kg (1.8kg)
Items per Package	25-Pads/Case	Pkg. Dimensions	57cm x 57cm x 9cm H
Container type	Carton		

Physical Properties:

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	290	30
Caliper	SPCTM-003A	mm	4,5	0.4
Absorbency ** (med. Oil)	SPCTM-004B	gL/gS	12.5	2
Tensile Strength	SPCTM-007	daN	7.3	0.7
Color	Visual	-----	White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.